



# SHENZHEN ANTISK TECHNOLOGY CO.LTD

## FY0501-RE ROHS 2.0 ESD Rubber Mat

Model	Description	Color	Additional note	Remark	Feature
FY0501-REDG	ROHS 2.0 ESD Rubber Mat ,Smooth,dull finish,200D-250D, 2 layer	Green	Top layer RS: <a href="#">106-8Ω</a> Friction electrostatic charge V<100 Bottom Layer:104-5Ω Friction electrostatic charge V<50	Width:0.6-1.2m Length:10m,12m Thickness:2mm Static Dissipative Layer:0.5mm Conductive Layer 1.5mm	1.Adopt high quality nature nitrile rubber material,stable Anti-electrostatic performance.Comply with ROHS 2.0
FY0501-REDY	ROHS 2.0 ESD Rubber Mat,Smooth,dull finish,200D-250D, 2 layer	Grey	Top layer RS: <a href="#">106-8Ω</a> Friction electrostatic charge V<100 Bottom Layer:104-5Ω Friction electrostatic charge V<50	Width:0.6-1.2m Length:10m,12m Thickness:2mm Static Dissipative Layer:0.5mm Conductive Layer 1.5mm	2.Stable Color
FY0501-REDB	ROHS 2.0 ESD Rubber Mat ,Smooth,dull finish,200D-250D, 2 layer	Blue	Top layer RS: <a href="#">106-8Ω</a> Friction electrostatic charge V<100 Bottom Layer:104-5Ω Friction electrostatic charge V<50	Width:0.6-1.2m Length:10m,12m Thickness:2mm Static Dissipative Layer:0.5mm Conductive Layer 1.5mm	3.Harding Wearing
FY0501-RESG	ROHS 2.0 ESD Rubber Mat Smooth,shiny finish,200D-250D, 2 layer	Green	Top layer RS: <a href="#">106-8Ω</a> Friction electrostatic charge V<100 Bottom Layer:104-5Ω Friction electrostatic charge V<50	Width:0.6-1.2m Length:10m,12m Thickness:2mm Static Dissipative Layer:0.5mm Conductive Layer 1.5mm	4.No shrinkage
FY0501-RESG	ROHS 2.0 ESD Rubber Mat smooth,shiny finish,200D-250D, 2 layer	Grey	Top layer RS: <a href="#">106-8Ω</a> Friction electrostatic charge V<100 Bottom Layer:104-5Ω Friction electrostatic charge V<50	Width:0.6-1.2m Length:10m,12m Thickness:2mm Static Dissipative Layer:0.5mm Conductive Layer 1.5mm	5.No smell,Heat resistance
FY0501-RESB	ROHS 2.0 ESD Rubber Mat ,smooth,shiny finish,200D-250D, 2 layer	Blue	Top layer RS: <a href="#">106-8Ω</a> Friction electrostatic charge V<100 Bottom Layer:104-5Ω Friction electrostatic charge V<50	Width:0.6-1.2m Length:10m,12m Thickness:2mm Static Dissipative Layer:0.5mm Conductive Layer 1.5mm	6.Soft/Flexible/Comfortable. Anti-skid